

# Chameleon Stack/Batch

Model SB218A / SB318A / SB418A



Web widths of 20", 30" and 42"

500 FPM standard; options up to 800 FPM

Inline or near-line operation

Tight web standard; slack web is optional

Integration with new or existing digital print production and finishing lines

Tight web management system ensures industry-leading stack quality and accuracy at offset speeds

Variable high speed stack and batch operation

Slack or tight web interface through EMT sheeter

Robust, offset-based design produces reliable stacking and batching of EMT sheeted product

Exact count reliability

Offset within stack

Optional deep pile stack

Delivery options inline folding or integrated mailroom or bindery processes

Optional 2D bar-code reader for intelligent stack applications

Optional EMT slit merge section for stacking of merged documents

Applications include:

- Roll-to-sheet to stack
- Roll-to-sheet to stack and fold
- Roll-to-sheet to stack and bind
- Direct mail
- Transactional documents
- Checks
- Postcards
- Folded signatures
- Book blocks
- Mailers
- Statements
- Manuals
- Ballots
- Inserters
- Brochures
- Coupons and vouchers



780 Centerline Drive • Hobart, WI 54155

Phone: 920.468.5475 • Fax: 920.468.7991

info@emtinternational.com • www.emtinternational.com

EMT Europe

Ahaus Germany

Phone: +49 00 02561 963 5865

Fax: +49 00 02561 963 5867

service@emteurope.de


EMT Worldwide Direct Service: +49 00 02561 963 5865 (8:00 am - 4:00 pm CET) | EMT Worldwide Direct Service: +00 1-920-227-8814 (4:00 pm - 12:00 am CET) | EMT Worldwide 24/7 Service: +00 1-920-360-4175 (12:00 am - 8:00 am CET)

# Chameleon Stack/Batch

Model SB218A/SB218A/SB418A



Stack and Batch



Stacking Printed Material



## General Information

Model Number	SB218A	SB318A	SB418A
<u>Features</u>			
Process one	Stack and Batch	Stack and Batch	Stack and Batch
<u>Utilities</u>			
Electrical	230V or 480V, 3ø 50/60Hz	230V or 480V, 3ø 50/60Hz	480V, 3ø 50/60Hz
Compressed Air	80 psi @ 5cfm	80 psi @ 5cfm	80 psi @ 5cfm
<u>Performance Speed</u>	50-500 fpm (15-152 mpm) <i>Option to 800 fpm</i>	50-500 fpm (15-152 mpm) <i>Option to 800 fpm</i>	50-600 fpm [15-182mpm] <i>Option to 800 fpm</i>
<u>Substrate</u>	67 to 200gsm (35-350gsm optional)	67 to 200gsm (35-350gsm optional)	67 to 200gsm (35-350gsm optional)
<u>Interface</u>	EMT CHS or SHS	EMT CHS or SHS	EMT CHS or SHS
<u>Paper length</u>	8.0" - 18.5" [204mm] - [470mm]	8.0" - 18.5" [204mm] - [470mm]	8.0" - 18.5" [204mm] - [470mm]
<u>Web Width</u>	6.5" - 20" [165-520mm]	15" - 30" [380-760mm]	16.0" - 42" [406-1066mm]
<u>Stack Height</u>	45 sheets - 12" Varies with paper weight	45 sheets - 12" Varies with paper weight	45 sheets - 12" Varies with paper weight
<u>Size</u>			
Length x Width x Height	L 178" x W 56" x H 59"	L 178" x W 56" x H 59"	L 178" x W 56" x H 59"
Weight Net	3007lbs [1364kg]	3608lbs [1637kg]	4690lbs [2127kg]
Weight Gross	3821lbs [1733kg]	4580lbs [2077kg]	5960lbs [2703kg]



780 Centerline Drive • Hobart, WI 54155  
 Phone: 920.468.5475 • Fax: 920.468.7991  
 info@emtinternational.com • www.emtinternational.com

EMT Europe  
 Ahaus Germany  
 Phone: +49 00 02561 963 5865  
 Fax: +49 00 02561 963 5867  
 service@emteurope.de