

Chameleon Perf

Model DP20 / DP30 / DP42



Web widths of 20", 30", and 42"

500 FPM standard; options up to 800 FPM

Inline and near-line operation

Tight web standard; slack web is optional

Integration with new or existing digital print production and finishing lines

Tight web management ensures highest speeds, tightest tolerances, and perforation accuracy

Pre-or post-print engine operation

EMT quick-change perf bars allow blade changes in seconds

Optional linear dynamic perforating

Dynamic perf available

Fold perforation module or section available as complement

Applications include:

Multiple-page statements

Phone bills

Financial statement

Coupons/vouchers

Transactional mail

Forms

Courtesy checks

Fold perf/assist

Educational workbooks

Special statements

Direct mail



780 Centerline Drive • Hobart, WI 54155

Phone: 920.468.5475 • Fax: 920.468.7991

info@emtinternational.com • www.emtinternational.com

EMT Europe

Ahaus Germany

Phone: +49 00 02561 963 5865

Fax: +49 00 02561 963 5867

service@emteurope.de


EMT Worldwide Direct Service: +49 00 02561 963 5865 (8:00 am - 4:00 pm CET) | EMT Worldwide Direct Service: +00 1-920-227-8814 (4:00 pm - 12:00 am CET) | EMT Worldwide 24/7 Service: +00 1-920-360-4175 (12:00 am - 8:00 am CET)

Chameleon Perf

Model DP20 / DP30 / DP42



EMT Exclusive Quick-Change Cross-Perf Bar



Cross-Perforated Paper



General Information

Model Number	DP20	DP30	DP42
Features			
Process one	Dynamic Cross Perf	Dynamic Cross Perf	Dynamic Cross Perf
Utilities			
Electrical	230V or 480V, 3ø 50/60Hz	230V or 480V, 3ø 50/60Hz	480V, 3ø 50/60Hz
Compressed Air	80 psi (5.5 bar), 2 CFM [56 L/min]	80 psi (5.5 bar), 2 CFM [56 L/min]	80 psi (5.5 bar), 2 CFM [56 L/min]
Performance Speed	50-500 fpm (15-152 mpm) <i>Option of up to 800 fpm</i>	50-500 fpm (15-152 mpm) <i>Option of up to 800 fpm</i>	50-600 fpm (15-182 mpm) <i>Option of up to 800 fpm</i>
Paper Length	4.0"-24.0"	4.0"-24.0"	4.0"-24.0"
Paper Range	67-200 gsm (35-350 gsm optional)	67-200 gsm (35-350 gsm optional)	67-200 gsm (35-350 gsm optional)
Web Width	6.5" - 20.5" (127 mm - 521 mm)	17.75" - 30" (203 mm - 762 mm)	16" - 42" (406 mm - 1067 mm)
Number of Lanes Up	2-up	3-up	4-up
Minimum Perf-to-Perf Distance	2.75" <i>Option of 2" min. Available in single cylinder. Option of 1" min. Available in multiple cylinders.</i>	2.75" <i>Option of 2" min. Available in single cylinder. Option of 1" min. Available in multiple cylinders.</i>	2.75" <i>Option of 2" min. Available in single cylinder. Option of 1" min. Available in multiple cylinders.</i>
Size			
Length x Width x Height	L 82" x W 70" x H 74"	L 84" x W 85" x H 78"	L 101" x W 198" x H 86"
Weight Net	3061lbs [1388kg]	3612lbs [1638kg]	5716lbs [2592kg]
Weight Gross	3547lbs [1609kg]	4199lbs [1905kg]	7052lbs [3198kg]



780 Centerline Drive • Hobart, WI 54155
 Phone: 920.468.5475 • Fax: 920.468.7991
 info@emtinternational.com • www.emtinternational.com

EMT Europe
 Ahaus Germany
 Phone: +49 00 02561 963 5865
 Fax: +49 00 02561 963 5867
 service@emteurope.de