

Chameleon Line Hole Punch

Model LHP20 / LHP30 / LHP42



Web widths of 20", 30" and 42"

500 FPM standard; options up to 800 FPM

Inline or near-line operation

Tight web standard; slack web is optional

Integration with new or existing digital print production and finishing lines

Pre- or post-print engine operation

Integrated drying technology

Roll inventory and offline hole punching

Reduce dust and hanging chad with precision EMT punch tooling

Eliminates the cost of pre-punched materials

Increase punch lifetime up to one year without changing punches and dies

Creates register line-hole punches for tractor-fed inserters and folders

Exclusive EMT long-life punch tooling

Optional file hole punching

Optional binding punch pattern

Tightest tolerances and punch accuracy

Applications include:

Tractor-fed rolls

Inserting

Folding

Transactional forms

Statements

Specialty bound books and manuals

EDP labels

Coupons and vouchers

Educational workbooks



780 Centerline Drive • Hobart, WI 54155

Phone: 920.468.5475 • Fax: 920.468.7991

info@emtinternational.com • www.emtinternational.com

EMT Europe

Ahaus Germany

Phone: +49 00 02561 963 5865


Fax: +49 00 02561 963 5867

service@emteurope.de

EMT Worldwide Direct Service: +49 00 02561 963 5865 (8:00 am - 4:00 pm CET) | EMT Worldwide Direct Service: +00 1-920-227-8814 (4:00 pm - 12:00 am CET) | EMT Worldwide 24/7 Service: +00 1-920-360-4175 (12:00 am - 8:00 am CET)

Chameleon Line Hole Punch

Model LHP20 / LHP30 / LHP42



Punch Rings



Punched Paper Application



General Information

Model Number	LHP20	LHP30	LHP42
Features			
Process one	Line Hole Punch	Line Hole Punch	Line Hole Punch
Utilities			
Electrical	230V or 480V, 3ø 50/60Hz	230V or 480V, 3ø 50/60Hz	480V 3Ø, 3ø 50/60Hz
Compressed Air	80psi @ 2cfm, 3/8 NPT connection	80psi @ 2cfm, 3/8 NPT connection	90psi @ 2cfm, 3/8 NPT connection
Performance Speed	50-500 fpm (15-152 mpm) <i>Option to 800 fpm</i>	50-500 fpm (15-152 mpm) <i>Option to 800 fpm</i>	50-500 fpm (15-182 mpm) <i>Option to 800 fpm</i>
Paper Range	67 to 200gsm (35-350gsm optional)	67 to 200gsm (35-350gsm optional)	67 to 200gsm (35-350gsm optional)
Web Width	6.5" - 20.5" [165-520mm]	15" - 30" [380-760mm]	16.0" - 42" [406-1066mm]
Hole Specification	5/32" [4mm] diameter line hole punching on 1/2" centers	5/32" [4mm] diameter line hole punching on 1/2" centers	5/32" [4mm] diameter line hole punching on 1/2" centers
Ring Sets	Two ring sets included to produce two rows of holes	Two ring sets included to produce two rows of holes	Four ring sets included to produce four rows of holes
Size			
Length x Width x Height	L 58" x W 70" x H 74"	L 84" x W 85" x H 78"	L 81" x W 96" x H 74"
Weight Net	2496lbs [1132kg]	3415lbs [1549kg]	5638lbs [2557kg]
Weight Gross	2858lbs [1296kg]	4002lbs [1815kg]	6425lbs [2914kg]



780 Centerline Drive • Hobart, WI 54155
 Phone: 920.468.5475 • Fax: 920.468.7991
 info@emtinternational.com • www.emtinternational.com

EMT Europe
 Ahaus Germany
 Phone: +49 00 02561 963 5865
 Fax: +49 00 02561 963 5867
 service@emteurope.de